

1 -

D:\Connect10.8\10.8.0\appserv\web\WEB-INF\web.xml

```
<!--
```

```
<filter>
```

```
<filter-name>NtlmAuthenticationFilter</filter-name>
```

```
<filter-class>com.macromedia.airspeed.servlet.filter.NtlmAuthenticationFilter</filter-class>
```

```
<init-param>
```

```
<param-name>ignore-pattern-0</param-name>
```

```
<param-value>/api/</param-value>
```

```
</init-param>
```

```
<init-param>
```

```
<param-name>ignore-pattern-1</param-name>
```

```
<param-value>/common/</param-value>
```

```
</init-param>
```

```
<init-param>
```

```
<param-name>ignore-pattern-2</param-name>
```

```
<param-value>/servlet/gateway</param-value>
```

```
</init-param>
```

```
<init-param>
```

```
<param-name>ignore-pattern-3</param-name>
```

```
<param-value>/servlet/mirror</param-value>
```

```
</init-param>
```

```
<init-param>
```

```
<param-name>ignore-pattern-4</param-name>
```

```
<param-value>/servlet/testbuilder</param-value>
```

```
</init-param>
```

```
<init-param>
  <param-name>ignore-pattern-5</param-name>
  <param-value>/main</param-value>
</init-param>
</filter>

<filter-mapping>
  <filter-name>NtlmAuthenticationFilter</filter-name>
  <url-pattern>/*</url-pattern>
</filter-mapping>
-->

<filter>
  <filter-name>HeaderAuthenticationFilter</filter-name>
  <filter-class>com.macromedia.airspeed.servlet.filter.HeaderAuthenticationFilter</filter-class>

  <!--
  <init-param>
    <param-name>ignore-pattern-0</param-name>
    <param-value>/api</param-value>
  </init-param>
-->

  <init-param>
    <param-name>ignore-pattern-1</param-name>
    <param-value>/common</param-value>
  </init-param>
```

```
<init-param>
  <param-name>ignore-pattern-2</param-name>
  <param-value>/servlet/gateway/</param-value>
</init-param>
<init-param>
  <param-name>ignore-pattern-3</param-name>
  <param-value>/servlet/mirror</param-value>
</init-param>
<init-param>
  <param-name>ignore-pattern-4</param-name>
  <param-value>/servlet/testbuilder</param-value>
</init-param>
<init-param>
  <param-name>ignore-pattern-5</param-name>
  <param-value>/main</param-value>
</init-param>
</filter>

<filter-mapping>
  <filter-name>HeaderAuthenticationFilter</filter-name>
  <url-pattern>/api/*</url-pattern>
</filter-mapping>
```

2 –

D:\Connect10.8\10.8.0\custome.ini

add this last line :

```
HTTP_AUTH_HEADER=x-user-id
```

3 -

start - stop all adobeconnect